



QMTS2.E136069

Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

See General Information for Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

ZHEJIANG HUAZHENG NEW MATERIAL CO LTD
 2 HUAYI RD YUHANG TOWN
 YUHANG DISTRICT
 HANGZHOU, ZHEJIANG 311121 CHINA

E136069

Industrial laminates:

Mtl Dsg	ANSI Type	Color	Build up		R.T.I.		H				Meets 746E DSR
			Min Thk (mm)	Flame Class	Elec (°C)	Mech (°C)	H W I	H A I	V T R	C T I	
Industrial laminates, furnished as sheets.											
H01, H1E-01											
	XPC	TN	0.71	HB	105	105	1	4	2	-	-
			1.45	HB	105	105	1	3	2	4	Yes
H130, FR4-74											
	FR-4	NC	0.38	V-0	130	130	0	3	-	-	Yes
			0.63	V-0	130	140	0	3	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	Yes
H140-1	FR-4	YL	0.38	V-0	130	130	0	0	5	-	Yes
			0.63	V-0	130	140	0	3	5	-	Yes
			1.4	V-0	130	140	0	2	5	4	Yes
H150	No ANSI	YL	0.38	V-0	-	-	-	-	-	-	-
H2130	No ANSI	NC	0.63	V-0	-	-	-	-	-	-	-
H2135hf	CEM-3	NC	0.63	V-0	130	140	0	2	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	Yes
Industrial laminates.											
H1170	FR-4	NC	0.38	V-0	130	130	0	3	-	-	Yes
			0.63	V-0	130	140	0	3	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	Yes
H1308	No ANSI	NC (YL)	0.38	V-0	-	-	-	-	-	-	-
			0.63	V-0	-	-	-	-	-	-	-
			1.40	V-0	-	-	-	-	-	-	-
H140A	FR-4	NC	0.38	V-0	130	130	0	3	-	-	Yes
			0.63	V-0	130	140	0	3	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	Yes

H140H	FR-4	NC	0.38	V-0	130	130	0	3	-	-	Yes
			0.63	V-0	130	140	0	3	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	Yes
H150(LF)	FR-4	NC	0.38	V-0	130	130	0	3	-	-	Yes
			0.63	V-0	130	140	0	3	-	-	Yes
			1.40	V-0	130	140	0	2	-	4	Yes
H1600	No ANSI	NC (YL)	0.63	V-0	-	-	-	-	-	-	-
			1.40	V-0	-	-	-	-	-	-	-
H170LF	No ANSI	NC (YL)	1.40	V-0	90	90	-	-	-	-	-
			0.63	V-0	90	90	-	-	-	-	-
			0.38	V-0	90	90	-	-	-	-	-
H2135	CEM-3	NC	0.63	V-0	130	140	0	2	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	Yes

Metal base industrial laminates:

Mtl Dsg	Color	Metal		Dielectric		R.T.I.		H			Meets 746E DSR		
		Min Thk (mm)		Min Thk (mic)	Max Thk (mic)	Flame Class	Elec (°C)	Mech (°C)	H W I	H A I		V T R	C T I
Aluminum base with Epoxy (EP) dielectric, industrial laminates, furnished as sheets.													
HA50, HA50PP													
	NC	0.7		75	400	V-0	90	90	4	0	-	0	Yes
Aluminum base with Epoxy (EP) dielectric, industrial laminates.													
HA40, HA40P\$													
	NC	0.80		75	190	V-0	-	-	-	-	-	-	-

Ultrathin build ups:

Build Up					Laminate			Prepreg		
Mtl Dsg	ANSI Type	Min Thk (mm)	TI Elec	TI Mech	Mtl Dsg	Thk (mic)	TI Elec	Mtl Dsg	Thk (mic)	TI Elec
Ultrathin industrial laminates and bonding layers, furnished in sheet form, for use in multilayer printed wiring boards where the thickness is built up to the minimum specified.										
H1170	FR-4	0.38	130	130	H1170	75	90	H1170P	75	90
		0.63	130	140	H1170	75	90	H1170P	75	90
H130, FR4-ML	FR-4	0.38	130	130	H130, FR4-ML	75	90	H130P, FR4-ML	75	90
H140-1	FR-4	0.38	130	130	H140-1	100	120	H140-1P, 7628, 1080, 2116	80	90
H140A	FR-4	0.38	130	130	H140A	75	90	H140AP	75	90
H140H	FR-4	0.38	130	130	H140H	75	90	H140HP	75	90
		0.63	130	140	H140H	75	90	H140HP	75	90
H150(LF)	FR-4	0.38	130	130	H150(LF)	75	90	H150P(LF)	75	90

Metal clad industrial laminates:

Metal Clad Dsg	Laminate Dsg	Pre-preg Dsg	ANSI Type	Bld up	Clad Cond Thk			Max	Flame Class	Max	Solder Lts	
				Min Thk (mm)	Min Ext (mic)	Max Ext (mic)	Max Int (mic)	Area Dia (mm)		Oper Temp (°C)	Temp (°C)	Time (sec)
Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides,												

furnished as sheets.												
H140-1												
	H140-1	H140-1P, 7628, 1080, 2116	FR-4	0.38	17	102	68	50.8	V-0	130	288	20
Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides.												
H1170	H1170	H1170P	FR-4	0.38	17	102	68	50.8	V-0	130	288	20
H140A	H140A	H140AP	FR-4	0.38	17	102	68	50.8	V-0	130	288	20
H140H	H140H	H140HP	FR-4	0.38	17	102	68	25.4	V-0	130	288	20
H150(LF)												
	H150(LF)	H150P(LF)	FR-4	0.38	17	102	68	50.8	V-0	130	288	20
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides, furnished as sheets.												
H01, H1E-01												
	H01, H1E-01	-	XPC	0.71	17	70	-	50.8	HB	105	260	10
H140-1												
	H140-1	-	FR-4	0.38	17	102	-	50.8	V-0	130	288	20
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides.												
H1170	H1170	-	FR-4	0.38	17	102	-	50.8	V-0	130	288	20
H140A	H140A	-	FR-4	0.38	17	102	-	50.8	V-0	130	288	20
H140H	H140H	-	FR-4	0.38	17	102	-	25.4	V-0	130	288	20
H150(LF)												
	H150(LF)	-	FR-4	0.38	17	102	-	50.8	V-0	130	288	20
H170LF												
	H170LF	-	No ANSI	0.38	17	102	-	50.8	V-0	90	288	20
H2135	H2135	-	CEM-3	0.63	17	102	-	25.4	V-0	130	260	30
H2135hf												
	H2135hf	-	CEM-3	0.63	17	102	-	50.8	V-0	130	260	30

Metal clad metal base industrial laminates:

Metal Clad Dsg	Lam-inate Dsg	Pre-preg Dsg	Metal		Dielectric		Clad Cond Thk			Max Area Dia (mm)	Flame Class	Max Oper Temp (°C)	Solder Lts	
			Min Thk (mm)	Max Thk (mm)	Min Thk (mic)	Max Thk (mic)	Min Ext (mic)	Max Ext (mic)	Max Int (mic)				Temp (°C)	Time (sec)
Aluminum base with Epoxy (EP) dielectric, Metal clad industrial laminates with copper on one side only, furnished as sheets.														
HA50	HA50	-	0.7		75	400	34	102	-	50.8	V-0	90	300	60

Metal clad industrial laminates (Flammability Only Recognition):

Metal Clad Dsg	Lam-inate Dsg	Pre-preg Dsg	ANSI Type	Bid up		Clad Cond Thk			Max Area Dia (mm)	Flame Class	Max Oper Temp (°C)	Solder Lts	
				Min Thk (mm)	Max Thk (mm)	Min Ext (mic)	Max Ext (mic)	Max Int (mic)				Temp (°C)	Time (sec)
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides, furnished as sheets (Flammability Only Recognition).													
H150	H150	-	No ANSI	0.38	-	-	-	-	-	V-0	-	288	20
H2130	H2130	-	No ANSI	0.63	-	-	-	-	-	V-0	-	260	10
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides (Flammability Only Recognition).													
H1308	H1308	-	No ANSI	0.38	-	-	-	-	-	V-0	-	288	20

H1600	H1600	-	No ANSI	0.63	-	-	-	-	-	V-0	-	288	20
-------	-------	---	---------	------	---	---	---	---	---	-----	---	-----	----

Metal clad metal base industrial laminates (Flammability Only Recognition):

Metal Clad Dsg	Lam-inate Dsg	Pre-preg Dsg	Metal	Dielectric		Clad Cond Thk			Max	Flame Class	Max	Solder Lts	
			Min Thk (mm)	Min Thk (mic)	Max Thk (mic)	Min Ext (mic)	Max Ext (mic)	Max Int (mic)	Area Dia (mm)		Oper Temp (°C)	Temp (°C)	Time (sec)
Aluminum base Metal clad industrial laminates with copper on one side only (Flammability Only Recognition).													
HA40	HA40	-	0.80	75	190	-	-	-	-	V-0	-	288	20

\$ - May be shipped as a B-stage insulation sheet without being adhered to a metal substrate. PWB manufacturer must adhere to aluminum metal base as specified above, within thickness range Recognized.



Marking: Company name or trademark and material designation on container or wrapper.
 Last Updated on 2012-01-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".